



## **EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, 1 stream, 4x mA**

**# de producto:** EZ3005.9700140T  
**USD Precio:** Contacto Hach Chile

### **The Challenge of Consistent Chloride Monitoring**

Chloride monitoring in municipal and industrial water can be disrupted by fouling, drift and temperature swings - creating extra maintenance and compliance risk. The EZ3005sc uses discontinuous ISE measurement with temperature control to deliver stable, precise chloride results with minimal operator intervention. Automated operation helps reduce routine maintenance and lower operating cost while keeping reliable chloride data available for process control.

Designed for straightforward integration, the analyser supports multiple analog and digital outputs - including Modbus, Profinet and Ethernet/IP - so you can bring results and diagnostics directly into your control system.

#### **Benefits:**

- Discontinuous ISE measurement with temperature control for repeatable results
- Automated operation reduces maintenance effort and operator time
- Efficient reagent use helps lower total cost of ownership
- Analog and digital connectivity: Modbus, Profinet and Ethernet/IP
- Real-time results and diagnostics to support compliance and process optimisation

#### **Reliable, Stable Measurements**

Avoid downtime from unreliable ISE data caused by temperature fluctuations. The EZ3005sc stabilises both sample and electrode using a temperature controlled flow cell, eliminating measurement errors and delivering precise, repeatable chloride results operators can trust.

#### **Lower Maintenance Effort**

Minimise downtime and service costs with the EZ3005sc. Automated 2 point calibration, reagent alerts, a rugged ISE electrode, and minimal moving parts extend maintenance intervals; so operators spend less time servicing instruments and more time on plant operations.

#### **Reduced Operating Cost**

The EZ3005sc helps optimise operating costs by reducing chemical consumption and service visits. Multi stream capability monitors up to eight sample lines, lowering cost per sampling point and extending equipment life.

#### **Designed for easy integration into existing control systems**

With a wide range of analogue and digital outputs, this analyser aligns with plant specific requirements, ensuring compatibility with existing infrastructure and immediate access to real time measurement data.

---

## Especificaciones

Agua de refrigeración:	Caudal aprox. 5 L/h; temperatura máx. 30 °C; presión máx. 0,5 bar
Agua desmineralizada:	Does not apply
Aire de instrumentación:	Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air. Used to flush the instrument in corrosive environment. Min. 0.2 bar - Max. 0.5 bar
Alimentación:	100 - 240 VAC, 50/60 Hz  Max. power consumption: 120 VA
Calibración:	Automatic; 2-point; Frequency freely programmable: 6 hours, 12 hours, daily, weekly. Note: manufacturer recommends that a calibration is done when the reagents are replaced
Calidad de muestra:	Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU
Caudal de muestra:	100 - 300 mL/min
Certificaciones:	CE, ETL certified to UL and CSA safety standards, UKCA
Conexión a tierra:	Earth connection Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm <sup>2</sup>
Contenido de la caja:	EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)
Dimensiones (A x A x P):	688 mm x 460 mm x 340 mm
Drenaje:	Atmospheric pressure, vented, min. Ø 32 mm
Garantía:	12 meses
Grado de protección:	IP44
Interferencias:	Bromide [(Br)-], sulphide [(S) <sup>2-</sup> ], iodide [(I)-], cyanide [(CN)-] ions may interfere. Mercury [(Hg)+] must be absent. Ammonia [NH <sub>3</sub> ] and thiosulphate [(S <sub>2</sub> O <sub>3</sub> ) <sup>2-</sup> ] may interfere. Fats, oil, proteins, surfactants and tar.
Límite de detección (LOD):	2 - 100 mg/L Cl <sup>-</sup> : 2 mg/L  5 - 250 mg/L Cl <sup>-</sup> : 5 mg/L  10 - 500 mg/L Cl <sup>-</sup> : 10 mg/L  20 - 1000 mg/L Cl <sup>-</sup> : 20 mg/L
Limpieza automática:	Sí; frecuencia programable a voluntad: cada 6 horas, cada 12 horas, diariamente, semanalmente
Material:	Hinged part: Thermoform ABS, Door: PMMA  Wall section: Galvanised steel, powder coated
Método de medición:	Discontinuous, direct measurement by combined Ion-Selective Electrode
Método de medida:	Ion-Selective Electrode
Número de corrientes de muestra:	Standard: 1  Optional accessory for 2, 4, or 8 sample streams
Parámetro:	Chloride
Peso:	Max. 35 kg (77 lb)
Precisión:	Better than 2% full scale range for standard test solutions
Presión de muestra:	By external overflow vessel (open to atmospheric pressure)
Rango de medición:	2 - 100 mg/L Cl <sup>-</sup>  5 - 250 mg/L Cl <sup>-</sup>  10 - 500 mg/L Cl <sup>-</sup>

	20 - 1000 mg/L Cl <sup>-</sup>
Requisitos de los reactivos:	Keep between 10 - 30 °C (50 - 86 °F)
Salidas analógicas:	Active 0 - 20 mA (or 4 - 20 mA) max. 500 Ohm load, standard 4, optional: 8
Salidas digitales:	Relays: 5 contacts, not user configurable: Malfunction, maintenance, analysis ready, sample ready, sample ready (EZ9150)
	Ethernet Connections: Optional: Claros Ethernet connection and Modbus TCP/IP Ethernet connector; LAN version; 10/100 Mbps or Profinet or Ethernet IP
	RS485 communication: Profibus DP or Modbus RTU
Temperatura ambiente:	10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing)
Temperatura de la muestra:	10 - 30 °C (50 - 86 °F)
Tiempo de ciclo:	Default: 5 minutes
	Continuous: 5 minutes
Validación:	Automatic; Frequency freely programmable: 6 hours, 12 hours, daily, weekly

---

## Contenido de la caja

EZ3005sc Chloride Ion-Selective Electrode (ISE) Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Electrode and Chloride Electrode, combined, and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)