



Be Right™



EZ3008sc Fluoride Ion-Selective Electrode (ISE) Analyser, 1 stream, 4x mA

de producto: EZ3008.9700140T
USD Precio: Contacto Hach Chile

Fluoride Monitoring for Operational Stability

Stable fluoride control is essential in drinking water and surface-water treatment, but manual sampling can be labor intensive and introduce variability. The EZ3008sc automates fluoride measurement using discontinuous ISE analysis with temperature-controlled readings for dependable, repeatable data. Gel-filled ISE technology eliminates electrolyte refilling, reducing routine service and helping lower total cost of ownership.

With multi-stream capability, optional grab sampling for spot checks, and seamless integration into SCADA/PLC/DCS, the analyser provides continuous results and diagnostics for confident compliance reporting and tighter process control.

Benefits:

- Temperature-controlled, discontinuous ISE analysis for repeatable fluoride results
- Gel-filled ISE electrodes eliminate electrolyte refilling
- Multi-stream monitoring and optional grab sampling for spot checks
- Reduced maintenance and service interventions
- Integrates with SCADA/PLC/DCS for real-time data and diagnostics

Stable Performance in Changing Conditions

The EZ3008sc delivers temperature controlled, discontinuous fluoride measurements with multi stream capability. Operators get stable, reliable data during process fluctuations, reducing manual checks and adjustments while maintaining confident day to day water quality control.

Reduced Maintenance and Service Costs

Designed for long-term operation, the analyser uses gel-filled ion-selective electrodes that eliminate the need for electrolyte refilling. This technology reduces reagent consumption, routine service interventions, maximises analyser uptime, and lowers the total cost of ownership over the instrument's lifetime.

Flexible Connectivity for Legacy and Modern Platforms

Integrate seamlessly into existing PLC, SCADA, DCS and plant network architectures with a built-in industrial panel PC. Real-time data transmission provides immediate visibility into diagnostics and status, enabling faster responses and improved decision-making across your facility.

Flexible Analysis for Multiple Streams

Conduct quick spot checks and investigations without interrupting routine monitoring using built-in grab sampling. When combined with the optional 8-channel sample stream, one analyser sequentially measures multiple process points: maximising asset utilization and coverage while simplifying your system architecture.

Especificaciones

| | |
|----------------------------------|---|
| Agua de refrigeración: | Caudal aprox. 5 L/h; temperatura máx. 30 °C; presión máx. 0,5 bar |
| Agua desmineralizada: | Does not apply |
| Aire de instrumentación: | Dry and oil free according to ISA-S7.0.01-1996 quality standard for instrument air. Used to flush the instrument in corrosive environment. Min. 0.2 bar - Max. 0.5 bar |
| Alimentación: | 100 - 240 VAC, 50/60 Hz Max. power consumption: 120 VA |
| Calibración: | Automatic; 2-point; Frequency freely programmable: 6 hours, 12 hours, daily, weekly. Note: manufacturer recommends that a calibration is done when the reagents are replaced |
| Calidad de muestra: | Maximum particle size 100 µm, < 0.1 g/L; Turbidity < 50 NTU |
| Caudal de muestra: | 100 - 300 mL/min |
| Certificaciones: | CE, ETL certified to UL and CSA safety standards, UKCA |
| Conexión a tierra: | Earth connection Dry and clean earth pole with low impedance (< 1 Ohm) using an earth cable of > 2.5 mm ² |
| Contenido de la caja: | EZ3008sc Fluoride Ion-Selective Electrode (ISE) Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Fluoride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution) |
| Dimensiones (A x A x P): | 688 mm x 460 mm x 340 mm |
| Drenaje: | Atmospheric pressure, vented, min. Ø 32 mm |
| Garantía: | 12 meses |
| Grado de protección: | IP44 |
| Interferencias: | Metal ions like aluminium [(Al) ³⁺] > 72 mg/L, calcium [(Ca) ²⁺] > 108 mg/L and iron [(Fe) ²⁺ /(Fe) ³⁺] > 150 mg/L. Fats, oil, proteins, surfactants and tar. |
| Límite de detección (LOD): | 0.05 - 2.5 mg/L F ⁻ : 0.05 mg/L 0.1 - 5 mg/L F ⁻ : 0.1 mg/L 0.2 - 10 mg/L F ⁻ : 0.2 mg/L |
| Limpieza automática: | Sí; frecuencia programable a voluntad: cada 6 horas, cada 12 horas, diariamente, semanalmente |
| Material: | Hinged part: Thermoform ABS, Door: PMMA Wall section: Galvanised steel, powder coated |
| Método de medición: | Discontinuous, direct measurement by combined Ion-Selective Electrode |
| Método de medida: | Ion-Selective Electrode |
| Número de corrientes de muestra: | Standard: 1 Optional accessory for 2, 4, or 8 sample streams |
| Parámetro: | Fluoride |
| Peso: | Max. 35 kg (77 lb) |
| Precisión: | Better than 2% full scale range for standard test solutions |
| Presión de muestra: | By external overflow vessel (open to atmospheric pressure) |
| Rango de medición: | 0.05 - 2.5 mg/L F ⁻ 0.1 - 5 mg/L F ⁻ 0.2 - 10 mg/L F ⁻ |
| Requisitos de los reactivos: | Keep between 10 - 30 °C (50 - 86 °F) |

| | |
|----------------------------|--|
| Salidas analógicas: | Active 0 - 20 mA (or 4 - 20 mA) max. 500 Ohm load, standard 4, optional: 8 |
| Salidas digitales: | Relays: 5 contacts, not user configurable: Malfuntion, maintenance, analysis ready, sample ready, sample ready (EZ9150) |
| | Ethernet Connections: Optional: Claros Ethernet connection and Modbus TCP/IP Ethernet connector; LAN version; 10/100 Mbps or Profinet or Ethernet IP |
| | RS485 communication: Profibus DP or Modbus RTU |
| Temperatura ambiente: | 10 - 30 °C ± 4 °C deviation at 5 - 95% relative humidity (non-condensing) |
| Temperatura de la muestra: | 10 - 30 °C (50 - 86 °F) |
| Tiempo de ciclo: | Default: 5 minutes |
| | Continuous: 5 minutes |
| Validación: | Automatic; Frequency freely programmable: 6 hours, 12 hours, daily, weekly |

Contenido de la caja

EZ3008sc Fluoride Ion-Selective Electrode (ISE) Analyser, Instruction Manual, 1 x Double Bit Door Key, 1 x Mounting Brackets, 1 x ISE Fluoride Electrode and 1 x empty 2.5L Reagent Container with Fittings (for Buffer Solution)